


Product Model : Mifare inlay card(2*5)

Product Name : Pre-lamination for ISO Card

Description : Pre-lamination for ISO Proximity Card is the best choice for printing ISO card applications.

Gamma offers the Pre-lamination in LF, HF and UHF band.

	<p>Applications: Pre-lamination for ISO Proximity Card is the best choice for printing ISO card applications.</p>
---	--

Preliminary Specification — Mifare inlay card(2*5)	
Mechanical Dimension	Depending on the model
Working Frequency	13.56MHz/ 125KHz / 860-960MHz
Reading Range	Depending on the band
Material	PVC
Operating Temperature	—
Storage Temperature	—
Approx. Weight	100g / sheet
Color	White
RoHS	Compliant
Enclosure rating	—
Assembly	—
Printing	—
Option	Customized Dimension
Packaging	200 sheets / carton
Available RFID Chip	
13.56 MHz —MIFARE S50 (1K), MIFARE S70(4K), MIFARE Ultralight, MIFARE DESFire V0.6, I.CODE SLI, MIFARE 1K compatible, Tag-it Plus, Tag-it Pro, Tag-it Standard	
125 KHz —WS4100, EM4200, EM4205/ EM4305, ATA5557, HITAG1 / 2, HITAG S256 / S2048	
860-960MHz, EPC Gen2 protocol – ISO/IEC 18000-6C Alien-H3/H4 ; Impinj-M3/M4	

If you need more information, please, visit our website www.microchip.ua